

1310/1550 High Power Single Stage Polarization Maintaining Optical Isolator



(patent pending)

DATASHEET

[Return to the Webpage](#)



1310/1550 high power polarization maintaining single stage optical isolator is a passive device that maintaining polarization while guiding light at 1310/1550 nm in the normal direction, and minimizing back reflection and back scattering in the reverse direction for any state of polarization. Employing Agiltron's proven advanced micro optics design, it features low insertion loss, high power handling, extremely high isolation, high extinction ratio, compact package and high stability. making them an ideal choice for application in fiber amplifier systems, optical fiber sensors and instrumentation.

Features

- Low Insertion Loss
- High Power Handling
- High Isolation
- Low PDL
- High Reliability
- Low Cost

Applications

- Optical Fiber Amplifier
- Fiber Optic Sensor
- Instrumentation



Specifications

| Parameter | Min | Typical | Max | Unit |
|--|-----------|-------------------------|------------|------|
| Operation Wavelength (λ_0) | 1310 | 1310 \pm 15 | | nm |
| | C Band | 1528 ~ 1564 | | |
| | L Band | 1570 ~ 1605 | | |
| Insertion Loss (Over λ_0 , 0~70°C, no connector) | | \leq 0.5 | \leq 0.7 | dB |
| Extinction Ratio (Over λ_0 , 0~70°C, no connector) | \geq 20 | | | dB |
| Extinction Ratio (λ_c , 23°C, no connector) | | \geq 25 | | dB |
| Channel Isolation (Over λ_0 , 0~70°C) ^[1] | \geq 32 | | | dB |
| Channel Isolation (λ_c , 23°C) | | \geq 42 | | dB |
| Return Loss (Input/Output, no connector) | \geq 50 | | | dB |
| Polarization Alignment | | Slow Axis | | |
| Operating Temperature | 0 | | +70 | °C |
| Storage Temperature | -40 | | +85 | °C |
| Optical Power Handling | | \leq 5 ^[2] | | W |
| Backwards Power Handling ^[1] | | 10 | 100 | % |

Notes:

- [1]. Regular Back Reflect 10% of forward power, over 10% requires special order.
- [2]. Continuous operation, for pulse operation call. Requiring mount the unit for heat dissipation.

Note: For a polarized input light version, the isolation is optimized to block the light reflection of the same polarization. Although lights of other polarizations may also be blocked, the extinction may be poor. PM isolators can be specially made to block backward propagating lights of all polarizations. PM isolators can also be made with a light polarizing function.

Warning: This is an OEM module designed for system integration. Do not touch the PCB by hand. The electrical static can kill the chips even without a power plug-in. Unpleasant electrical shock may also be felt. For laboratory use, please buy a Turnkey system.

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 03/06/26

[+1 781-935-1200](tel:+17819351200)

sales@agiltron.com

www.agiltron.com


1310/1550 High Power Single Stage Polarization Maintaining Optical Isolator



(patent pending)

DATASHEET

Mechanical Dimensions (mm)



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Ordering Information (Part Number)

| Prefix | Type | Wavelength | Grade | Package | Fiber Type | Fiber Cover | Fiber Length | Connector ^[1] |
|--------|--|---|-----------------------------|----------------------------|---------------------------|---|--|--------------------------|
| | 3 0 | | | | | | | 1* |
| OIHP- | Polarization Maintaining Single stage = 30 | 1310 = 3 C Band = C L Band = L Special = 0 | Standard = 1 Special = 0 | ø5.5x40 = 1 Special = 0 | PM1550 = B Special = 0 | Bare Fiber = 1 900µm Loose Tube = 3 Special = 0 | 0.25m = 1 0.5m = 2 1.0m = 3 Special = 0 | |

* Agiltron provide high power connector, please call.

[1]. The connector cannot be installed directly onto bare fiber, as it is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer can remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SM28 fiber and decreases further with smaller core fibers.

Application Notes

Fiber Core Alignment

Note that the minimum attenuation for these devices depends on excellent core-to-core alignment when the connectors are mated. This is crucial for shorter wavelengths with smaller fiber core diameters that can increase the loss of many decibels above the specification if they are not perfectly aligned. Different vendors' connectors may not mate well with each other, especially for angled APC.

Fiber Cleanliness

Fibers with smaller core diameters (<5 µm) must be kept extremely clean, contamination at fiber-fiber interfaces, combined with the high optical power density, can lead to significant optical damage. This type of damage usually requires re-polishing or replacement of the connector.

Maximum Optical Input Power

Due to their small fiber core diameters for short wavelength and high photon energies, the damage thresholds for device is substantially reduced than the common 1550nm fiber. To avoid damage to the exposed fiber end faces and internal components, the optical input power should never exceed 20 mW for wavelengths shorter 650nm. We produce a special version to increase the how handling by expanding the core side at the fiber ends.




1310/1550 High Power Single Stage Polarization Maintaining Optical Isolator



(patent pending)

DATASHEET

Typical Wavelength Dependence for Single Stage



1310/1550 High Power Single Stage Polarization Maintaining Optical Isolator



(patent pending)

DATASHEET

Typical Wavelength Dependence for Dual Stage

