

BUY NOW 

PermLock™ Fiber Optic Mechanical Splicing Tool Kit

Fiber splices made easy, reliable, and low cost
(patent pending)

Product Description

The Optowares's *PermLock™ Fiber Optic Mechanical Splice* is the latest technology to connect two fibers easily and reliably without the use of fusion splicing. Designed for aerospace applications, it offers a hazard-free environment, absence of spark, high voltage, and heat. Moreover the glass sealed splice offers low optical loss, wide-temperature operation, 25-year service life, and low cost of ownership. The patent pending design enables fiber self-alignment with high repeatability. A "light-bridging" material fills the fiber gap for stable, ultra low loss splice. Optowares supplies a hand-held and battery powered curing kit for quick and easy cleave and splicing, even with polyimide coating fiber. PermLock™ Fiber Optic Splice has passed the most stringent aerospace qualification. The splice has several outer-jacket options suited for various applications. This product is well suited for applications in aerospace, shipboard/submarine, mining, and communication networks, as well as field optical fiber repair and fiber-to-home installation.

Features

- Low Insertion Loss
- Low Reflection Loss
- Easy to Use
- High Reliability
- Rugged
- Spark Free
- Low Cost



Specification

Mechanical Splicing Tool Kit	Typical	Unit
Dimension	420 x 300 x 110	cm
Weight	9.5	LB

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Applications

- LAN/MAN/WAN
- Military
- Aerospace
- Field Use
- Mining